



Fowler offers you several QC Printers. Our QC Printer #54-903-211, still offered as an integral part of the Digitrix/Max-Cal Measuring System, has been modified to accept a wide variety of Fowler electronic gages with output.

In addition to the Digitrix and Max-Cal line, the older Universal QC Printer #54-903-210 can be used with other Fowler gages with output, including: Ultra-Cal II electronics, Ultra-Digit I & II, Trimos minivertical I and Bowers Electronic Holmike I

### Special Features:

- Provides hard copy output of all measurements, including histograms and statistical data of up to 999 samples.
- Dimensions of Printer: 4" x 7" x 1<sup>1</sup>/<sub>2</sub>".
- Allows cancellation of last measurement taken. The next correct measurement will automatically be given the last sample number with no break in sequence.
- Uses 1<sup>3</sup>/<sub>8</sub>" thermal paper.
- Operates on AC power only.
- Price includes footswitch, AC adaptor, thermal paper and fitted case.

### Functions of Printer:

The Universal QC Printer provides hard copy output of sample measurements (numerates up to 999 samples and indicates if a reading is above/below tolerance limits); average (mean) values; maximum and minimum values; range; standard deviation; sample standard deviation; number of parts above/below tolerance; process capability; percent defective. Red & green signal lights indicate "go/no-go" condition of measured parts. Printer will chart a histogram, displaying bin values, bin width and the number of measurements in each bin.



Order No.	Description
<b>54-903-210</b>	Universal QC Printer (Includes AC adaptor & footswitch).
<b>54-903-211</b>	Universal QC Printer for use with Digitrix and Max-Cal.
<b>54-903-213</b>	Replacement footswitch (w/80" length cable).
<b>54-903-212</b>	Replacement AC adaptor (120V).
<b>54-903-215</b>	Replacement thermal paper (5 rolls per box).
<b>54-902-112</b>	20" connect cable, 5 pin for Max-Cal/Digitrix series.
<b>54-902-113</b>	80" connect cable, 5 pin for Max-Cal/Digitrix series.
<b>54-902-114</b>	120" connect cable, 5 pin for Max-Cal/Digitrix series.
<b>54-902-115</b>	20" N/S 14 pin cable for Max-Cal/Digitrix series.
<b>54-902-116</b>	80" N/S 14 pin cable for Max-Cal/Digitrix series.
<b>54-903-001</b>	Cable for Ultra-Cal II and Electronic Holmike Mark I
<b>54-903-002</b>	Cable for Minivertical I
<b>54-903-003</b>	Cable for Ultra Digit I & II