

Fowler

Outside Inch Micrometers



No. 52-253-001.



The Fowler No. 52-253 series of outside micrometers features exceptional quality and accuracy.

Distinct figures and graduations on the non-glare, satin chrome background permit easy reading, and the ribbed frame allows for measuring with extra ease and comfort.

Special Features:

- Hammertone blue baked enamel finish.
- Microfine graduations on satin chrome finish and carbide tipped measuring faces.
- Graduation = .001".
- Includes standard with sizes 2" and over.
- Diameter of measuring faces = .256".
- Friction or ratchet stop thimble for exact and repetitive readings.
- Flatness = .00003".
- Accuracy = .0001" for 0-1".
- Parallelism = .00005" for 0-1".
- Positive lever locking clamp ensures reliable measurement.
- Anvil & spindle hardened and precision ground with microlap finish on tips.
- All micrometers meet or exceed U.S. Federal specifications for accuracy.
- Price includes a wrench and fitted case.



Order No.	Range	Graduation	Thimble Style
52-253-001	0—1"	.001"	Friction
52-253-101	0—1"	.001"	Ratchet
52-253-002	1—2"	.001" w/standard	Friction
52-253-102	1—2"	.001" w/standard	Ratchet
52-253-003	2—3"	.001" w/standard	Ratchet
52-253-004	3—4"	.001" w/standard	Ratchet
52-253-005	4—5"	.001" w/standard	Ratchet
52-253-006	5—6"	.001" w/standard	Ratchet
Sets:			
52-253-400	0—4"	.001" w/standards	
52-253-600	0—6"	.001" w/standards	

Fowler

Outside Inch Micrometers.



No. 52-240-001.



The Fowler No. 52-240 series offers a wide variety of sizes to cover a range of measuring needs.

Fowler micrometers are of the finest quality available—at prices that defy competition. Special care in design and workmanship create a long lasting precision tool.

Special Features:

- Hammertone blue baked enamel finish.
- Microfine graduations on satin chrome finish and carbide tipped measuring faces;
- Diameter of measuring faces = .256".
- Friction or ratchet stop thimble for exact and repetitive readings.
- Flatness = .00003"; accuracy = .0001" for 0-1"; parallelism = .00005" for 0-1".
- Quick, easy zero adjustment on sleeve.
- Positive lever locking clamp.
- Spindle thread hardened, ground and lapped for ultimate accuracy.
- Anvil & spindle hardened and precision ground with microlap finish on tips.
- Meets or exceeds Federal accuracy specs.
- Price includes a wrench and fitted case.



Order No.	Range	Graduation	Thimble
52-240-001	0—1"	.0001"	Friction
52-240-101	0—1"	.0001"	Ratchet
52-240-002	1—2"	.0001" w/standard	Friction
52-240-102	1—2"	.0001" w/standard	Ratchet
52-240-003	2—3"	.0001" w/standard	Ratchet
52-240-004	3—4"	.0001" w/standard	Ratchet
52-240-005	4—5"	.0001" w/standard	Ratchet
52-240-006	5—6"	.0001" w/standard	Ratchet
52-240-007	6—7"	.0001" w/standard	Ratchet
52-240-008	7—8"	.0001" w/standard	Ratchet
52-240-009	8—9"	.0001" w/standard	Ratchet
52-240-010	9—10"	.0001" w/standard	Ratchet
52-240-011	10—11"	.0001" w/standard	Ratchet
52-240-012	11—12"	.0001" w/standard	Ratchet