



▲ *External Dial Calipers #52-554-800 series allow clearance over such obstructions as flanges, pipes, etc.*



Made in
ENGLAND



▲ *Use Internal Dial Calipers #52-554-700 series for extended reach.*



▲ *External Dial Calipers #52-554-600 and 900 series are for use where access is limited.*



Fowler External Dial Calipers are direct reading instruments for fast checking of casting dimensions prior to machining. Alternately, when the External Dial Caliper Gage is set to a standard, it may be used as a comparator for checking large parts. Its versatility makes it a must for all shops.

Special Features:

- Available with throat depths with a capacity of 5¹/₄"—22" .
- Large clear graduations.
- Easy one hand operation.
- Furnished in 2 graduations: .01" or .001".
- Revolution counter provided on dial gage.
- Bezel rotates 360° for easy zero setting.
- Carbide tipped anvils.



Order No.	Throat Depth	Throat Clearance	Range	Grad.	Accuracy	Anvil Type
External Calipers						
52-554-800	5 ¹ / ₄ "	2.5"	0—2"	.01"	±.01"	Pin
52-554-801	5 ¹ / ₄ "	2.5"	0—2"	.001"	±.005"	Pin
52-554-802	9 ¹ / ₄ "	2.5"	0—2"	.01"	±.01"	Pin
52-554-803	9 ¹ / ₄ "	2.5"	0—2"	.001"	±.005"	Pin
52-554-822	22"	2.25"	0—2"	.01"	±.02"	Pin
Internal Calipers						
52-554-701	5"	-	.875—2.875"	.001"	±.005"	Ball
52-554-700	5"	-	.875—2.875"	.01"	±.01"	Ball
External Calipers for limited access areas						
52-554-601*	6"	1" closed 3" open	0—2"	.001"	±.005"	Ball & Pin
52-554-600*	6"	1" closed 3" open	0—2"	.01"	±.01"	Ball & Pin
52-554-901*	10"	1" closed 3" open	0—2"	.001"	±.005"	Ball & Pin
52-554-900*	10"	1" closed 3" open	0—2"	.01"	±.01"	Ball & Pin
52-554-922*	22"	1" closed 3" open	0—2"	.01"	±.02"	Pin

*These models are supplied with interchangeable anvils.

