

Fowler

Sylvac External Measuring Stands



▲ Horizontal unit shown with Digital Display Unit #54-618-140 and probe #54-618-444.

5
YEAR WARRANTY

Fowler/Sylvac External Measuring Stand is ideal for measuring small parts.

Specifications

Overall range	.787" (20mm)
Measuring range	.393" (10mm)
Accuracy	.00004" (1µm) with probe #54-618-444
	.0002" 5µm with dial gage
Measuring force	0.3—1N + force of the probe
Lifting lever	Left or right
Operating	Horizontal or vertical position
Output	RS232
Dimensions	6 x 2.75 x 2"
	(150 x 70 x 55mm)
Clamping diameter	8mm
Weight	1.9kg



◆ #54-618-216 shown with #54-520-876 indicator.



Order No.	Description
54-618-215	Horizontal Measuring Stand
54-618-216	Vertical Measuring Stand
Accessories	
54-618-170	Supporting Table—adjustable X,Y,Z
54-618-171	Table for vertical position
54-618-172	Turn table with 25 holes from 0.2—5mm
54-618-173	Lifting device with pedal
54-520-791*	Mark IV Indicator, 1/2" (12.5mm) travel. Same as #54-520-790 except it has 8mm diameter stem. Contact point thread is M2.5.
54-520-876*	Mark V Indicator, 1/2" (12.5mm) travel. Same as #54-520-875 except it has 8mm diameter stem. Contact point thread is M2.5.