MICROMETERS

Outside Micrometers

Series 101





Features

- Satin-finished chrome frame, tapered (on the anvil side) for hard-to-reach places.
- Carbide-tipped measuring faces.

Accuracy

- Flatness: .000024"/0.6µm
- Parallelism:
 - .00005" for up to .59"/1.3 μ m for up to 15mm, .00008" for up to 3"/2 μ m for up to 75mm, .00012" for up to 4"/3 μ m for up to 100mm.
- Designed to be operated efficiently with one hand.



Designed to be operated efficiently with one hand.



Specifications

Outside Micrometers

Inch

IIICII				
Order No.	Range	Resolution	Accuracy	Remarks
101–230	05"	.0001"	±.0001"	Ratchet Stop
101–113	0–1"	.0001"	±.0001"	Ratchet Stop
101–114	1–2"	.0001"	±.0001"	Ratchet Stop with Standard
101–119	2–3"	.0001"	±.0001"	Ratchet Stop with Standard
101–120	3–4"	.0001"	±.00015"	Ratchet Stop with Standard
101–117	0–1"	.0001"	±.0001"	Friction Thimble
101–118	1–2"	.0001"	±.0001"	Friction Thimble with Standard
101–105	0–1"	.001"	±.0001"	Ratchet Stop
101–106	1–2"	.001"	±.0001"	Ratchet Stop with Standard
101–109	0–1"	.001"	±.0001"	Friction Thimble
101–110	1–2"	.001"	±.0001"	Friction Thimble with Standard